

## IOboard-A4i2o-D8i4o Ethernet Industrial IO Module

IOboard-A4i2o-D8i4o is an interface for 4 analog inputs, 2 analog outputs, 8 digital inputs and 4 digital outputs (optoisolated). Housed in a DIN rail mountable case with industrial screw terminals, IOboard-1 modules are connected to a control computer via Ethernet and TCP/IP, and feature smart firmware to configure the device, to read and set IO lines and to set event triggers.

IOboard modules are interfaces for analog and digital I/O signals over Ethernet. Digital I/O provides monitoring and control of high/low, or open/close industrial devices. Analog inputs and outputs support a wide variety of industrial devices. High resolution, low noise, A/D and D/A converters deliver high accuracy and reliability. Isolation assures high system performance and electrical security.

### Features

4 Analog Inputs:	<ul style="list-style-type: none"><li>• user selectable range:<ul style="list-style-type: none"><li>◦ -10 to 10 V</li><li>◦ 0 to 20 ma</li></ul></li><li>• Resolution: 24Bit</li><li>• Accuracy:<ul style="list-style-type: none"><li>◦ voltage input <math>\pm 0.01\%</math></li><li>◦ current input <math>\pm 0.1\%</math></li></ul></li><li>• Input impedance:<ul style="list-style-type: none"><li>◦ voltage input 100k<math>\Omega</math> min</li><li>◦ current input 250<math>\Omega</math> <math>\pm 0.1\%</math></li></ul></li></ul>
2 Analog Outputs:	<ul style="list-style-type: none"><li>• user selectable range<ul style="list-style-type: none"><li>◦ -10 to 10 V</li><li>◦ 0 to 20 ma</li></ul></li><li>• Resolution: 12Bit</li><li>• Accuracy: 0.2% typical</li><li>• No missing code 12</li><li>• Output current: 5mA nominal, 15mA short circuit</li><li>• Output resistance: 0.2<math>\Omega</math> max</li></ul>
8 Digital Inputs	<ul style="list-style-type: none"><li>• 6 to +24V opto-isolated</li><li>• Input current: 10<math>\mu</math>A</li></ul>
4 Digital Outputs	<ul style="list-style-type: none"><li>• 6 to +24V opto-isolated</li><li>• Output current: 100mA</li></ul>
Communication:	EtherNet 10BaseT with user-configurable IP address.
Protocol:	TCP using two channels: Control and Event. Other protocols can be implemented.
Power requirements:	24V DC (4W)
Environment:	<ul style="list-style-type: none"><li>• operating temperature: 0 to 40°C</li><li>• storage temperature: -10 to 50°C</li><li>• rel. humidity: 10 to 60%</li></ul>
Dimensions:	105Wx86Hx58Dmm (4.1"Wx3.4"Hx2.3"D)
Approvals:	EN 61131-2:2007, CE
Warranty:	3 years parts and labour