

IOboard-D12i6o Ethernet Industrial IO Module

IOboard-D12i6o is an interface for 12 digital inputs and 6 digital outputs (optoisolated). Housed in a DIN rail mountable case with industrial screw terminals, IOboard-1 modules are connected to a control computer via Ethernet and TCP/IP, and feature smart firmware to configure the device, to read and set IO lines and to set event triggers.

IOboard modules are interfaces for analog and digital I/O signals over Ethernet. Digital I/O provides monitoring and control of high/low, or open/close industrial devices. Analog inputs and outputs support a wide variety of industrial devices. High resolution, low noise, A/D and D/A converters deliver high accuracy and reliability. Isolation assures high system performance and electrical security.

Features

12 Digital Inputs	<ul style="list-style-type: none">• 6 to +24V opto-isolated• Input current: 10µA
6 Digital Outputs	<ul style="list-style-type: none">• 6 to +24V opto-isolated• Output current: 100mA
Communication:	EtherNet 10BaseT with user-configurable IP address.
Protocol:	TCP using two channels: Control and Event. Other protocols can be implemented.
Power requirements:	24V DC (4W)
Environment:	<ul style="list-style-type: none">• operating temperature: 0 to 40°C• storage temperature: -10 to 50°C• rel. humidity: 10 to 60%
Dimensions:	105Wx86Hx58Dmm (4.1"Wx3.4"Hx2.3"D)
Approvals:	EN 61131-2:2007, CE
Warranty:	3 years parts and labour